YBERTM + RX BLUE FRAME - CLEAR HC ANTI - MIST LENS

TECHNICAL SPECIFICATION

EYE & FACE PROTECTION

PRODUCT CODE: ASU210-001-300

SCRATCH RESISTANT WRAPAROUND SINGLE PIECE LENS WITH RX ADAPTOR INSERT



CYBER™ FEATURES & PERFORMANCE

Lens and frame offer protection against low energy high-speed particles at 45 m/s (101mph)

The optical qualities of the lens comply with the requirements of optical class 1 (highest)

Anti-mist properties

Scratch resistant

Wraparound single piece lens

Duo-flex side arms with soft grip pads hold the spectacle comfortably in place

Available with easy fitting RX prescription insert

CLEANING & MAINTENANCE

The safety spectacles may be cleaned with soap and warm water and dried with a soft cloth

Do not clean with chemical or abrasive cleaners

The eye shield should be stored out of direct sunlight, away from chemicals and not exposed to extremes of temperature



Conforms to EN 166.1.F (K or N) & EN 170

EC Certificate Number 726, issued by Inspec Certification Limited















CYBERTM + RX BLUE FRAME - CLEAR HC ANTI - MIST LENS

TECHNICAL SPECIFICATION

EYE & FACE PROTECTION

PRODUCT CODE: ASU210-001-300

SCRATCH RESISTANT WRAPAROUND SINGLE PIECE LENS WITH RX ADAPTOR INSERT

CYBER™ RX MATERIALS

Frame: TR 90

Hard Nose Piece: Polycarbonate

Soft Nose Piece: PVC

Sponge: CR

CYBER™ RX FRAME OPTIONS

Colour Options:

Clear Only



DIMENSIONS OF CYBER™ RX

Width of lens groove: 1.8mm

Depth of lens groove: 1.3mm

PD: 68mm

Lens Base: 6mm curve

Lens size vertical: 35.8mm

Lens size diagonal: 47.9mm

Overall width: 124mm

Closest point between lens: 25.5mm

Weight: 6g

CYBER™ RX FEATURES

Dual lens frame for prescription lens

Universal fit with snap-in soft pad

Lightweight RX adaptor for Cyber Safety Spectacles

Suitable for prescription lens less than -3.5 Diopters



















YBERTM + RX BLUE FRAME - CLEAR HC ANTI - MIST LENS

TECHNICAL **SPECIFICATION**

EYE & FACE PROTECTION


PRODUCT CODE: ASU210-001-300

SCRATCH RESISTANT WRAPAROUND SINGLE PIECE LENS WITH RX ADAPTOR INSERT

DIMENSIONS OF INNER PACKAGING

Quantity: 10

Weight: 524g (Approx.)





HEIGHT: 112mm

DIMENSIONS OF SPECTACLE

Lens Thickness: 3mm

Lens Size (Vertical): 51mm

Lens Size (Diagonal): 175mm

Bridge: 23mm

Temple Length (Lens to tip): 122mm

Overall Width: 153mm


Closest point between temple tips: 71mm

Weight: 27g (Approx.)

DIMENSIONS OF OUTER PACKAGING

Quantity: 120

Weight: 7.5kg (Approx.)



HEIGHT: 482mm

LIMITATIONS OF USE

Protection will only be offered if the safety spectacles are fitted correctly

If the safety spectacles become scratched or damaged they should be replaced, likewise if the safety spectacles are subjected to severe impact they should be replaced immediately

Do not apply paint, solvents, adhesives or self-adhesive labels, except in accordance with instructions from the manufacturer

The safety spectacles, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the eye shield and seek medical advice

The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer

The Cyber™ is not suitable for protection against dusts, liquids or molten metals

MARKINGS

Frame: EN166 1.F

Clear Lens: 1.FN 2 - 1.21.F

Silver Lens: 5-2.5















